

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : 75W-110 Gear Oil  
 Product code : 00630, 00631, 00620, 00617

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gear Oil

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Driven Racing Oil  
 8649 Hacks Cross Rd  
 Olive Branch, MS 38654 - USA  
 T 866-611-1820

##### Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Asp. Tox. 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

May be fatal if swallowed and enters airways

Precautionary statements (GHS) :

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
Distillates, petroleum, hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7	53
1-Octene	(CAS-No.) 111-66-0	40

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.

# 75W-110 Gear Oil

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
Reactivity	: No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray or fog for cooling exposed containers.
--------------------------------	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.
Other information	: Spilled material may present a slipping hazard.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures	: Wash contaminated clothing before reuse. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.
--------------------	---

# 75W-110 Gear Oil

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Not applicable

##### 1-Octene (111-66-0)

Not applicable

#### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Wear eye/face protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Golden
Odour	: Mild
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 180 °C (356 °F) Typical
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.87 (15.6 °C / 60 °F)
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 15.5 cSt (100 °C / 212 °F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

# 75W-110 Gear Oil

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

#### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 15 g/kg
LD50 dermal rabbit	> 5000 mg/kg (no deaths occurred)

#### 1-Octene (111-66-0)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 10 g/kg
LC50 inhalation rat	8050 ppm/4h

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified.

STOT-single exposure : Not classified.

STOT-repeated exposure : Not classified.

Aspiration hazard : May be fatal if swallowed and enters airways.

#### 75W-110 Gear Oil

Viscosity, kinematic (calculated value)	15.5 mm <sup>2</sup> /s (100 °C / 212 °F)
---	---

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

# 75W-110 Gear Oil

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 12.2. Persistence and degradability

75W-110 Gear Oil	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

75W-110 Gear Oil	
Bioaccumulative potential	Not established.

1-Octene (111-66-0)	
Partition coefficient n-octanol/water	4.57 (at 25 °C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. The generation of waste should be avoided or minimized wherever possible.

## SECTION 14: Transport information

### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

## SECTION 15: Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product contains 2-Propenoic Acid known to the state of California to cause cancer, developmental and/or reproductive harm.

## SECTION 16: Other information

Revision date : 06/09/2017  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*